

IN THE CLAIMS:

Please amend the claims as follows.

1. (Currently amended) A computer network system, comprising:
a circuit board forming a backplane;
[[a]] at least one field replaceable unit (FRU) slot located on said backplane;
a bus;
a central resource coupled with said FRU slot via said bus, wherein said central resource is configured to generate a client-ID, wherein said client-ID is associated with said FRU slot; and
a non-volatile memory coupled to said central resource, wherein said client-ID is stored in said non-volatile memory;
~~wherein said central resource generates a client-ID; and~~
~~wherein said client-ID is associated with said FRU slot~~
wherein, when an FRU is connected to said FRU slot, said central resource is configured to retrieve said client-ID and provide said client-ID to said FRU, wherein said FRU is configured to download said client-ID via said bus.
2. (Original) The computer network system of claim 1, wherein said FRU slot comprises a Compact Peripheral Component Interconnect (CPCI) slot.
3. (Cancelled)
4. (Original) The computer network system of claim 1, wherein said client-ID comprises one of a serial number, part number, and a geographical address of said FRU slot.
5. (Original) The computer network system of claim 1, wherein said client-ID comprises a unique identifier and wherein said unique identifier prevents an FRU from clashing with other network devices.

6. (Original) The computer network system of claim 1, wherein said client-ID comprises a client-id utilized by an address protocol for assigning dynamic Internet Protocol (IP) addresses.
7. (Original) The computer network system of claim 6, wherein said address protocol comprises a Dynamic Host Configuration Protocol (DHCP).
8. (Original) The computer network system of claim 1, further comprises an FRU held by said FRU slot.
9. (Cancelled)
10. (Currently amended) The computer network system of claim ~~[[9]]~~ 8, wherein said client-ID can be downloaded by said FRU via said bus.
11. (Original) The computer network system of claim 10, wherein said FRU uses an Intelligent Platform Management Interface (IPMI) protocol to download said client-ID from said non-volatile memory via said bus.
12. (Original) The computer network system of claim 10, wherein said FRU uses said client-id for Dynamic Host Configuration Protocol (DHCP) booting.
13. (Currently amended) The computer network system of claim ~~[[9]]~~ 1, wherein said central resource retrieves and makes said client-id available to a new FRU and wherein said new FRU downloads said client-ID via said bus when said new FRU is held by said FRU slot.
14. (Original) The computer network system of claim 1, further comprising a second FRU slot located on said backplane and wherein said central resource generates a second client-ID.

15. (Original) The computer network system of claim 14, wherein said client-ID is uniquely generated by said central resource for said FRU slot and said second client-ID is uniquely generated by said central resource for said second FRU slot.
16. (Original) A method for client-ID generation on a computer network system, comprising:
 - generating a client-ID via a central resource;
 - associating said client-ID with a field replaceable unit (FRU) slot;
 - storing said associated client-ID in a non-volatile memory;
 - providing said stored client-ID to an FRU via an interface; and
 - utilizing said client-ID by said FRU.
17. (Original) The method of claim 16, wherein said FRU is inserted into said FRU slot associated with said client-ID.
18. (Original) The method of claim 16, wherein said utilizing said client-ID by said FRU comprises utilizing said client-ID as a client-ID field for Dynamic Host Configuration Protocol (DHCP) booting.
19. (Original) The method of claim 16, further comprising:
 - determining whether said FRU is to be replaced by a new FRU;
 - retrieving and making said client-ID available to said new FRU; and
 - downloading said client-id by said new FRU.
20. (Cancelled)